

PosiTector® Inspection

Unrivalled probe interchangeability

Visit us at
booth #46

Coating Thickness Probes

- Ferrous ■ Non-Ferrous ■ Combination ■ Ultrasonic

Surface Profile Probes

- Depth Micrometer ■ Replica Tape Reader

Environmental Conditions Probes

- Integral ■ Cabled Magnetic Probe ■ Anemometer Probe
- 1/2" NPT ■ Infrared

Hardness Probes

- Shore ■ Barcol

Salt Contamination Probe

- Bresle Method

Gloss

- 60° ■ 20°/60° ■ 20°/60°/85°

Ultrasonic Wall Thickness Probes

- Corrosion ■ Multiple Echo Thru-Paint ■ Precision
- Low Frequency ■ Xtreme



Available on the
App Store



Customized Inspection Kits...

Build your own kit from a selection of gage bodies and probes to suit your needs.



Coating
Thickness



Surface
Profile



Environmental
Conditions



Hardness



Salt
Contamination



Ultrasonic
Wall Thickness



Backwards Compatibility! The PosiTector gage accepts ALL coating thickness (6000/200), environmental (DPM), surface profile (SPG/RTR), salt contamination (SST), hardness (SHD/BHI), gloss (GLS), and ultrasonic wall thickness (UTG) probes manufactured since 2012.

DeFelsko®
The Measure of Quality

DeFelsko Corporation • Ogdensburg, New York USA
Tel: +1-315-393-4450 • Email: techsale@defelsko.com
1-800-448-3835 • www.defelsko.com

Made in U.S.A.